

### Super helper of small and medium-sized meeting room

The Yealink CP860 IP conference phone is a perfect choice for small and medium-sized conference room and can meet the demands of up to 16 people with optional expansion microphones. The CP860 provides many important audio features including optimal HD technology, build-in 3 microphone arrays, full-duplex technology and acoustic echo cancelling. This means that all users can enjoy rich, clear and life-like conference calls. The Yealink CP860 also supports call recording, plus linkages to mobile phones or PCs for a more convenient conference call experience

#### Key Features and Benefits

##### Optimal HD voice

The CP860's optimal HD voice, full duplex technology and acoustic echo cancelling mean that users can enjoy zero-distance communication with all other participants in every location.

##### Outstanding voice pickup

With its build-in 3 microphone arrays and outstanding audio performance, the CP860 provides up to 10-feet and 360° voice pickup as standard, with broader coverage using up to two optional expansion microphones. This allows users to move around freely in the conference room without affecting the voice quality.

##### Multiway conference, more flexible collaboration

Up to five participants can join any conference call. This significantly improves communication between users who are in different regions.

##### Super helper for call recording

Users can plug in a USB flash drive very easily to record important conference calls.

##### Seamless connection to mobile phones or PCs

Users can also connect their mobile phones or PCs to the CP860 with ease to share conference calls.



Optimal HD Voice



Expansion microphone



5-way conferencing



Call recording



Mobile phone /PC linkage

- Optimal HD voice, full duplex technology
- 10-feet and 360 degree voice pickup
- Optional expansion microphones for wider reception
- 320ms echo cancellation tail length
- Connect to a mobile phone or PC for conference calls
- 5-way conferencing support
- USB call recording support

### Audio features

- Optimal HD voice
- 10-feet (3-meter) microphone pickup, applie to medium-sized conference room
- Built-in 3 microphone arrays, 360 degree voice pickup
- 112 mm diameter and 2.7w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G.722, G.711 (A/μ), G.729AB, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, PLC, AJB, AGC

### Phone features

- 1 VoIP account
- Call hold, mute, DND
- Call recording, hotline
- 5-way conference calls
- Redial, call waiting, emergency call
- Call forward, call transfer, call return, dial plan
- Ring tone selection/ import/ delete
- Set date time manually or automatically
- Volume adjustment

### Directory

- Loal phonebook up to 1000 entries
- XML/ LDAP remote phonebook
- Intelligent search method
- Phonebook search/ import/ export
- Call history: dialed/ received/ missed/ forwarded
- Black list

### IP-PBX Features

- Intercom, multicast paging
- Anonymous call, anonymous call rejection
- Voice mail, distinctive ringtone, call pickup

### Display

- 192x64-pixel graphical LCD with backlight
- 24 total keys: 4 soft keys, off-hook key, on-hook key, redial, mute, volume key, 2 navigation keys, OK key
- Phone lock
- National language selection
- Caller ID with name, number
- LCD display logo

### Interface

- 1 x RJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af ), class 0
- 2 x EX mic port
- 1 x USB2.0 port
- 1 x mobile phone/PC port: 3.5mm
- 1 x Security lock port

### Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X

### Management

- Setup wizard
- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069, SNMP
- Reset to factory, reboot
- Package tracing export, system log

### Other physical features

- 4 context-sensitive "soft" keys
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A Output
- Power consumption (PSU): 2.7-5.6W
- Power consumption (PoE): 3.9-8.1W
- Dimension(W\*D\*H): 320mm\*260m\*52mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C (+14~122°F)

### Package features

- Package content:
  - Yealink CP860 IP conference phone
  - Ethernet Cable
  - Mobile Device Cable (3.5mm Jack)
  - Quick Start Guide
  - Power Adapter
- Qty/CTN: 5PCS
- N.W/CTN: 8.9KG
- G.W/CTN: 9.9KG
- Giftbox size: 334mm\*365mm\*96mm
- Carton Meas: 500mm\*379mm\*342mm

### Certification

